




SPECIFICATIONS





- Voltage rating: 250V AC, DC
- Current rating: 7A, AC, DC
- Withstanding Voltage: 1500V AC/minute
- Insulation resistance: 1000MΩmin
- Temperature range: -25°C~+85°C
- Contact resistance: Initial value/10mΩmax
- After envirommental testing/20mΩmax

HOUSING

- Part No.:J3961H
- Material:Nylon 66 UL 94V-0
- Suitable HLB J3961T series Terminal
- Mates with HLB J3961 series Wafer
- Q'ty:1000 pcs/bag

Poles	Part No	Dimensions (mm)	
		A	B
2	J3961-02	3.96	8.29
3	J3961-03	7.92	12.25
4	J3961-04	11.88	16.21
5	J3961-05	15.84	20.17
6	J3961-06	19.80	24.13
7	J3961-07	23.76	28.09
8	J3961-08	27.72	32.05
9	J3961-09	31.68	36.01
10	J3961-10	35.64	39.97
11	J3961-11	39.60	43.93
12	J3961-12	43.56	47.89
13	J3961-13	47.52	51.85
14	J3961-14	51.48	55.81
15	J3961-15	55.44	59.77

							GENERAL TOLERANCE X ±0.30 XX ±0.20 XXX ±0.10	东莞市翰皓精密电子有限公司 Dongguan HanHao Precision Electronics Co.,Ltd				PART NO.			
												J3961H-XX			
2010/08/22	A	B		Modify frame format	Jove	Jove Lau		APPROVAL		CHECK	DRAWN	DATA	TITLE 3.96 mm Crimp Style Connectors		
DATE	OLD REV	NEW REV	ECN	DESCRIPTION	CHECK	APPROVAL	PROJECT 	Smrk	Yu wei	Liu Yan	2010/08/22	UNIT mm	SCALE 1 : 1	NUMBER	REV B



■ SPECIFICATIONS

- Voltage rating: 250V AC, DC
- Current rating: 7A, AC, DC
- Withstanding Voltage: 1500V AC/minute
- Insulation resistance: 1000M Ω min
- Temperature range: -25°C~+85°C
- Contact resistance: Initial value/10m Ω max
- After envirommental testing/20m Ω max






■ HOUSING

- Part No.:J3961
- Material:Nylon 66 UL 94V-0
- Suitable HLB J3961T series Terminal
- Mates with HLB J3961 series Wafer
- Q'ty:1000 pcs/bag

Poles	Part No	Dimensions (mm)	
		A	B
2	J3961HB-02	3.96	8.02
3	J3961HB-03	7.92	11.98
4	J3961HB-04	11.88	15.94
5	J3961HB-05	15.84	19.90
6	J3961HB-06	19.80	23.86
7	J3961HB07	23.76	27.82
8	J3961HB-08	27.72	31.78
9	J3961HB-09	31.68	35.74
10	J3961HB-10	35.64	39.70
11	J3961HB-11	39.60	43.66
12	J3961HB-12	43.56	47.62
13	J3961HB-13	47.52	51.58
14	J3961HB-14	51.48	55.54
15	J3961HB-15	55.44	59.50

A

							GENERAL TOLERANCE X ±0.30 XX ±0.20 XXX ±0.10	东莞市翰皓精密电子有限公司 Dongguan HanHao Precision Electronics Co.,Ltd				PART NO. J3961HB-XX											
												TITLE 3.96 mm Crimp Style Connectors											
2010/08/22	A	B		Modify frame format	Jova	Jova Lau		APPROVAL	CHECK	DRAWN	DATA												
DATE	OLD REV	NEW REV	ECN	DESCRIPTION	CHECK	APPROVAL	PROJECT 	Smak	Yu wei	Liu Yan	2010/08/22	UNIT mm	SCALE 1 : 1	NUMBER 8	REV B								
1			2			3			4			5			6			7			8		



■ Specifications

- Voltage rating: 250V AC DC
- Current rating: 7A AC, DC
- Withstanding voltage: 1500V AC/minute
- Insulation resistance: 1000M Ω min.
- Temperature range: -25°C to +85°C
(Including temperature rise in applying electrical current)
- Applicable PC board thickness: 0.063" (1.6mm)
- Contact resistance: Initial value/10m Ω max.
After environmental testing/20m Ω max.

■ Terminal

- Part No.: J3961T
- Applicable wires: AWG#18-22
- Material: Brass
- Finish: Tin plated
- Hardness: SH
- Thickness: 0.25mm
- Used in HLB J3963 series Housing
- Q'ty: 3000pcs/reel

A

							GENERAL TOLERANCE X ±0.30 XX ±0.20 XXX ±0.10 PROJECT	东莞市翰皓精密电子有限公司				PART NO.			
								Dongguan HanHao Precision Electronics Co.,Ltd				J3961T			
2010/08/22	A	B		Modify frame format	Jove	Jove Lau		APPROVAL	CHECK	DRAWN	DATA	TITLE			
												3.96 mm Crimp Style Connectors			
DATE	OLD REV	NEW REV	ECN	DESCRIPTION	CHECK	APPROVAL					UNIT	SCALE	NUMBER	REV	
	1		2								mm	1:1	8	B	

1 2 3 4 5 6 7 8

F



E

D




C

B

A



Recommend PCB Layout



SPECIFICATIONS

- Voltage rating:250V AV DC
- Current rating:7A AC,DC
- Withstanding voltage:1500V AC/minute
- Insulation resistance:1000MΩmin.
- Temperature range:-25°C to+85°C
(Including temperature rise in applying electrical current)
- Applicable PC board thickness:0.063"(1.6mm)
- Contact resistance:Initial value/10mΩmax.
After environmental testing/20mΩmax.





WAFER

- Part No.J3961WR
- Material:Conctact:Brass,Tin plated
Base:Nylon 66 UL 94V-0
- Mates with HLB J3961 series Housing
- Q'ty:1000 pcs/bag

Polcs	Part No	Dimensions (mm)	
		A	B
2	J3961WR-02	3.96	8.01
3	J3961WR-03	7.92	11.97
4	J3961WR-04	11.88	15.93
5	J3961WR-05	15.84	19.89
6	J3961WR-06	19.80	23.85
7	J3961WR-07	23.76	27.81
8	J3961WR-08	27.72	31.77
9	J3961WR-09	31.68	35.73
10	J3961WR-10	35.64	39.69
11	J3961WR-11	39.60	43.65
12	J3961WR-12	43.56	47.61
13	J3961WR-13	47.52	51.57
14	J3961WR-14	51.48	55.53
15	J3961WR-15	55.44	59.49

							GENERAL TOLERANCE X ±0.30 XX ±0.20 XXX ±0.10	东莞市翰皓精密电子有限公司 Dongguan HanHao Precision Electronics Co.,Ltd				PART NO. J3961WR-XX			
												TITLE 3.96 mm Crimp Style Connectors			
2010/08/22	A	B		Modify frame format	Jova	Jova Lau			APPROVAL	CHECK	DRAWN	DATA	UNIT mm	SCALE 1 : 1	NUMBER
DATE	OLD REV	NEW REV	ECN	DESCRIPTION	CHECK	APPROVAL	PROJECT 	Smark	Yu wei	Liu Yan	2010/08/22				

1 2 3 4 5 6 7 8



■ Specifications

- Voltage Rating: 250V AC / DC
- Current Rating: 7A AC / DC
- Withstanding Voltage: 1500V AC/minute
- Insulation Resistance: 1000M Ω Min.
- Temperature Range: -25°C~+85°C
- Contact Resistance: Initial value/10m Ω Max.
After Enviornmental Testing/20m Ω Max.

■ Wafer

- Part No.: J3961WRB
- Material: Nylon or PBT UL94V-0
- Q'ty: 1,000 Pcs/Bag

A

							GENERAL TOLERANCE X ±0.30 XX ±0.20 XXX ±0.10	东莞市翰皓精密电子有限公司 Dongguan HanHao Precision Electronics Co.,Ltd				PART NO. J3961WRB-02			
												TITLE 3.96 mm Crimp Style Connectors			
2010/08/22	A	B		Modify frame format	Jove	Jove Lau		APPROVAL	CHECK	DRAWN	DATA				
DATE	OLD REV	NEW REV	ECN	DESCRIPTION	CHECK	APPROVAL	PROJECT 	Smak	Yu wei	Liu Yan	2010/08/22	UNIT mm	SCALE 1 : 1	NUMBER 8	REV B
1		2		3		4		5		6		7		8	